



UNITROL 30-TON REMOTE CHILLERS

Model #8550R, 8550RL, 8551R, 8551RL, 8556R, 8556RL

AUTOMOTIVE GRADE chillers designed to operate 24/7 under the most demanding industrial conditions.

MODULE DESIGN: Consists of three 10-ton remote outside condensers and one inside module with water pump, evaporators, and controls.

- **NOMINAL CAPACITY:** 360,000 BTU/Hr (105 KW, 30 tons) @90°F ambient
- **CONTROL:** Digital temperature controller, staged for maximum efficiency, digital temperature readout
OPTION: Dew Point protection system to prevent temperature setting below dew point of room
- **PUMP** 7.5HP centrifugal stainless steel with a maximum output of 180gpm @35psi
OPTION (L): Low flow water pump 3 gpm with a maximum output of 50gpm @35psi
- **BYPASS:** Internal pressure set allows low external water usage without freezing evaporator
- **EVAPORATOR:** Stainless steel brazed plate, external to water tank
- **CONDENSERS:** Air-cooled dual fan horizontal intake and exhaust in weather-proof galvanized steel outside enclosures.
- **FILTERS:** Water return flushable strainer
- **WATER TANK:** 90-gallon seamless non-metallic. 40-gallon tank is used for L low-flow option chillers
- **WATER MAKEUP:** Automatic water float valve
- **SAFETY SYSTEM:** Low Water Flow interlock switch
 Low and High Freon Safety systems and indicating lights
 Overload protection for compressors and water pump
- **ANTI-FLOW BACK WATER SYSTEM:** Solenoid valve and check valve prevents flooding when chiller is turned off.
- **SERVICE HOT ABILITY:** Can be inspected and serviced while running with all panels removed
- **POWER SERVICE:** MODEL 8550R = 460/3. Inside = 10A, Outside modules:3 = 20A each
 MODEL 8550RL = 460/3. Inside = 4A, Outside modules: 3 = 20A each
 MODEL 8551R = 230/3. Inside = 19A, Outside modules:3 =40A each
 MODEL 8551RL = 230/3. Inside = 8A, Outside modules:3 =40A each
 MODEL 8556R = 575/3. Inside = 9A, Outside modules: 3 =16A each
 MODEL 8556RL = 575/3. Inside = 3A, Outside modules: 3 = 6A each
- **SIZE:** Inside module = 50" X 52" X 44" (LXWXH). Three outside modules = 50" X 48" X 45" (LXWXH)
- **WEIGHT:** Inside module = 350lb. Three outside modules = 1,250lb

UNITROL ELECTRONICS, INC.

702 LANDWEHR ROAD

NORTHBROOK, ILLINOIS 60062

847-480-0115 sales@unitrol-electronics.com